

# Data sheet



Spec	Description
Fixed Port	16*100M/1Gb SFP 8*100M/1Gb SFP COMBO 8*10/100/1000Base-TX RJ45 COMBO 4*1G/10Gb SFP+
Network Protocol	IEEE 802.3 IEEE 802.3u 100BASE-TX IEEE 802.3ab1000BASE-T IEEE 802.3x IEEE 802.3z 1000BASE-X IEEE 802.3ad IEEE 802.3q 、 IEEE 802.3q/p IEEE 802.1w、 IEEE 802.1d 、 IEEE 802.1S STP(Spanning Tree Protocol) RSTP/MSTP( Rapid Spanning Tree Protocol)
Transmission Mode	Store and Forward(full wirespeed)
CPU	800MHz or 1Ghz
Jumbo frame	Jumbo frame up to 9K
Bandwidth	512Gbps
Packet Forwarding	92.32Mpps
MAC Address	16K
Buffer	4.1Mbit SRAM Packet Buffer
FLASH	512MB
RAM	512MB
Watt	≤36W
LED Indicator	PWR:Power LED SYS⊙System LED) 1~24:Link/ACT LED+ 1G LED 25-28: LINK/ATC+10G LED
Power	Redundant dual power input Built-in power AC 100~240V 50/60HZ
Operating Temperature/Humidity	-20~+55°C; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH Non coagulation
Product size/ (L*W*H)	440mm*255mm*45mm
N.W/G.W (kg)	3.6kg/4.5kg
Installation	Rack-mount(optional machine hanger spare parts)
Lightning protection level	6KV 8/20us; IP30
Certificate	CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS; KC
Warranty	Whole device for 1 year(Accessories not included)

## Data sheet

Features	L3 Switch
<b>Port</b>	
Port Shutdown	Support
Port Speed	Support autonegotiate, full-1000, full-100, half-100, full-10, half-10
Flow Control	support full-duplex IEEE 802.3x, half-duplex back pressure
Storm Control	Supports rate limit for broadcast, multicast, and DLF packets
Storm Constrain	Support the detection of broadcast packets, multicast packets, or unicast packets on the port, shutdown the port if the rate is over the threshold.
Port Mirror	Support
Port Rate Limit	Support port ingress and egress rate limit
Link Aggregation	<p>Support manual link aggregation</p> <p>Support LACP dynamic link aggregation</p> <p>Supports up to 32 aggregation groups, each group up to 8 ports</p> <p>Support source MAC, destination MAC, source destination MAC, source IP, destination IP, source destination IP routing strategy</p>
Port Isolate	Support
Jumbo Frame	Support up to 16KB packet
Redundant Port	Support
<b>MAC</b>	
MAC Table Capacity	16K
MAC Table Management	Support
Forwarding mode	Support IVL forwarding mode
Static MAC Address	Support
MAC Address Binding	Support
MAC Address Filtering	Support
MAC Learning Control	Control the MAC learning based on port
<b>VLAN</b>	
Number of VLANs	4K
802.1q-based VLAN	Support
MAC-based VLAN	Support
IP-based VLAN	Support
Protocol-based VLAN	Support
Voice VLAN	Support
VLAN Mapping	Support 1:1 mapping
QinQ	<p>Support basic QinQ</p> <p>Support flexible QinQ</p>
<b>Reliability</b>	
Spanning Tree Protocol	Support STP/RSTP/MSTP
Port Loop Detection	Support
EAPS	Support
ERPS	Support G.8032/Y.1344
LLDP	Support LLDP & LLDP-MED
UDLD	Fully compatible with CISCO's UDLD protocol
VLLP (VRRP Layer-2 Loop Protection)	Support, Only used with VRRP

## Data sheet

<b>L3</b>	
ARP	Support static and dynamic ARP
Static Route	Support
VLAN Interface	Support 32 VLAN interfaces
RIP	Support RIP v1/v2
OSPF	Support OSPFv2
Policy Route	Support
VRRP	Support
<b>Multicast</b>	
Static Multicast MAC Address	Support
IGMP SNOOPING	Support IGMP SNOOPING v1/v2/v3 Support IGMP Querier Support IGMP SNOOPING Filter
MVR	Support
GMRP	Support
<b>ACL</b>	
Standard IP-based ACL	Support
Extended IP based ACL	Support
MAC IP-based ACL	Support
MAC ARP-based ACL	Support
ACL Port Filtering	Support
Time-based ACL	Support
<b>QoS</b>	
Port Queue Number	8
Port Queue Scheduling Mode	Support WRR, RR, WDRR, SP
Port-based Classification	Support
802.1p-based Classification	Support
DSCP-based Classification	Support
ACL-based Classification	Support
QoS Policy	Support packets mapping to queue Support COS or DSCP Remarking Support rate limits of data flow Support data flow statistics Support mirroring of data flow
<b>DHCP</b>	
DHCP Client	Support
DHCP Snooping	Support
DHCP Relay	Support
DHCP Server	Support
DHCP option 82	Support
<b>Management</b>	
CLI Management	Support Console, Telnet and SSH
WEB Management	Support HTTP and HTTPS
SNMP Management	Support SNMP v1, v2c Support SNMP TRAP Support lots of standard and private MIBs
User Management	Support multiple user management
Log Management	Support local log management Support SYSLOG
RMON	Support RMON 1, 2, 3 and 9 groups

## Data sheet

Cluster Management	<p>Support NDP</p> <p>Support NTDP</p> <p>Support manual and automatic joining of cluster groups</p> <p>Support cluster unified management</p>
Configuration File	Support uploading and downloading configuration file
Upgrade software	Support
Clock Management	<p>Support local clock management</p> <p>Support SNTP</p>
<b>Security</b>	
Switch Management Security	<p>Support enabling and disabling TELNET, WEB and SNMP services</p> <p>Support TELNET, WEB and SNMP services to bind to standard IP ACLs</p> <p>Support for limiting the number of TELNET connections</p>
CPU Protection	The switch's own security protection prevents large data streams from attacking the switch itself.
AAA	<p>Support 802.1x</p> <p>Support RADIUS</p> <p>Supports authentication, authorization, and accounting through RADIUS server</p> <p>Support port-based and MAC-based 802.1x</p> <p>Support 802.1x guest VLAN</p>
IP MAC Binding	Support static configuration of IP, MAC and port binding
DHCP SNOOPING	<p>Support dynamic ARP binding to prevent ARP spoofing</p> <p>Support dynamic IP, MAC and port binding</p> <p>Support fixed port to connect to DHCP server to prevent private connection to DHCP server</p>
Prevent ARP Spoofing	<p>Support manually configuring MAC ARP-based ACL rules to prevent ARP spoofing.</p> <p>Support the DHCP SNOOPING function. During the process of obtaining an IP address by DHCP, the switch dynamically binds ARP to the port to prevent ARP spoofing.</p>
<b>POE</b>	
Switch Control	Support POE powering of ports on and off
Power Control	Support setting total power
Other Advanced Features	Support POE scheduling policy and PD online query, etc.
<b>Debugging</b>	
PING	Support
TRACEROUTE	Support
TELNET Client	Support