

16-Port Gigabit Switch

SL-1016GL



16x 10/100/1000Mbps RJ45

Loop Alarm Supported

Support Auto MDI/MDIX

Support Port Isolation, Extender Mode

Port 1-8 Support QoS data Priority

Specification	
Interface	16* 10/100/1000Mbps RJ45 Port
Standard	IEEE802.3(10Base-T) IEEE802.3u(100Base-TX) IEEE 802.3ab (1000Base-TX) IEEE802.3x (flow control)
Performance	
Switching Capacity	32Gbps
Throughput	23.8Mbps
Mac address	8K
Packet buffer	4M

Data sheet

indication	
Dip Switch	Default : 네트워크 표준 사용모드, 루프 알람 지원 Vlan : Port isolation Mode, 1~14 번포트 각포트끼리 통신 방지, 15~16 번 포트를 통해서만 통신가능 Extend : 1~14 번포트 전송거리 최대 250Meter, 설정시 속도 10Mbps 하향조절됨
Led indicator	PWR, Loop, Link, 1000M
Working Environment	Working Temperature : -10~50°C Storage Temperature : -40~70°C Working Humidity : 10%~90% , non-condensing Storage Temperature : 5%~90% , non-condensing
Size	270*180*45mm
Power	AC100~240V 50/60Hz
Packing list	본체, 랙 마운트킷, 파워코드, 매뉴얼

Order info	
SL-1016GL	16-Port Gigabit intelligent Ethernet Switch