

24-Port Gigabit Switch

SL-1024GS



24x 10/100/1000Mbps RJ45

9K Jumbo frame support

Support Auto MDI/MDIX

Support Port Isolation, Extender Mode

Specification	
Interface	24* 10/100/1000Mbps RJ45 Port
Standard	IEEE802.3(10Base-T) IEEE802.3u(100Base-TX) IEEE 802.3ab (1000Base-TX) IEEE802.3x (flow control)
Performance	
Switching Capacity	56Gbps
Throughput	40.32Mbps

Data sheet

Mack address	8K
Packet buffer	4.1M
indication	
Dip Switch	N : 네트워크 표준 사용모드 V : Port isolation Mode, 1~22 번포트 각포트끼리 통신 방지, 23~24 번 포트를 통해서만 통신가능 C : Flow control mode,(CCTV Mode)
Led indicator	PWR, Loop, Link, 1000M
Working Environment	Working Temperature : -10~55°C Storage Temperature : -40~75°C Working Humidity : 10%~90% , non-condensing Storage Temperature : 5%~90% , non-condensing
Size	305*140*45mm
Power	AC100~240V 50/60Hz
Packing list	본체, 랙 마운트킷, 파워코드, 매뉴얼

Order info

SL-1024GS	24-Port Gigabit Ethernet Switch
-----------	---------------------------------