


Data sheet

| | |
|--|---|
| Model | SL-2016GS |
|  | |
| Product | 16 Port Gigabit Ethernet Switch |
| Fixed Port | 16*10/100/1000Base-TX RJ45 port (Data) |
| Function | N:(standard normal) V:(port isolation) C:(Flow Control mode) |
| Network Protocol | IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x IEEE 802.1q |
| Transmission Mode | Store and Forward |
| Bandwidth | 56Gbps |
| Packet Forwarding | 40.32Mpps Supports 9K jumbo frame transmission |
| MAC Address | 8K |
| Buffer | 4.1M |
| Watt | Standby Power Consumption: ≤15W; |
| LED Indicator | PWR:Power LED 1-16:(Link LED=10/100M、1000M=Gigabit Link) |
| Power Input | Built-in Power AC: 100 ~ 240V 50-60Hz 1A |
| Operating Temperature/Humidity | -10 ~ +55°C; 5% ~ 90% RH Non coagulation |
| Storage Temperature/Humidity | -40 ~ +75°C; 5% ~ 95% RH Non coagulation |
| Product size/Packing size (L*W*H) | 210mm*105mm*45mm (Rack mount support) |
| Weight | 0.6kg/1kg |
| Installation | Desktop |
| Lightning protection level | 3KV 8/20us; IP30 |
| Certificate | CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS; KC |
| Warranty | 1year |