



Model	SL-2028GSFP
Product	Full Gigabit 26+2 Rack-mount Switch
Fixed Port	24*10/100/1000Base-TX RJ45 port (Data) 2*10/100/1000Base-TX uplink RJ45 port (Data) 2*1000M SFP
Network Protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3z 1000BASE-X IEEE 802.3x
Port Specification	10/100/1000BaseT (X) Auto
Transmission Mode	Store and Forward(full wirespeed)
Bandwidth	56Gbps
Packet Forwarding	40.32Mpps Supports 9K jumbo packet length forwarding at wire speed
MAC Address	8K
Buffer	4.1M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter) 1000BASE-SX:62.5μm/50μm MMF(2m~550m) 1000BASE-LX:62.5μm/50μm MM(2m~550m) or 10μm SMF(2m~5000m)
Watt	Standby Power Consumption : ≤30W ;
LED Indicator	PWR:Power LED 1-26:(Link LED =10/100M Link、1000M=Gigabit Link) 27 28:(SFP LED)
Power Input	Built-in Power AC: 100~240V 50-60Hz 1A
Operating Temperature/Humidity	-10 ~ +55°C ; 5% ~ 90% RH Non coagulation
Storage Temperature/Humidity	-40 ~ +75°C ; 5% ~ 95% RH Non coagulation

Data sheet

Productsize (L*W*H)	440mm*140mm*45mm
N.W/G.W (kg)	1.6kg/2.2kg
Installation	Rack-mount
Lightning protection level	3KV 8/20us ; IP30
Certificate	CE mark, commercial ; CE/LVD EN60950 ; FCC Part 15 Class B ; RoHS ; KC
Warranty	1 년 무상