

SL-POE3110TP



Model	SL-POE3110TP
Product	Full Gigabit 8 Port Built-in PoE Switch
Fixed Port	8*10/100/1000Base-TX PoE port (Data/Power) 2*10/100/1000Base-TX uplink RJ45 port (Data)
PoE Ports	1-8 port supports PoE
DIP Switch	N : standard mode V:1-8 ports isolation S:Long distance transmission 250m@10Mbps
Network Protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x IEEE 802.3af/at
PoE Pin	IEEE802.3af/at
Port Specification	10/100/1000BaseT (X) Auto
Transmission Mode	Store and Forward(full wirespeed)
Bandwidth	20Gbps
Packet Forwarding	14.44Mpps
MAC Address	2K
Buffer	2.5M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter)
Power Pin	Default 1/2(+), 3/6(-); Optional order 4/5(+), 7/8(-)
Single port power	Average 15.4W ; MAX 30W
Total power/Input voltage	MAX 150W (AC100-240V 50/60HZ)
Watt	Standby Power Consumption : ≤8W ;
LED Indicator	POWER:Power LED Uplink:(Link LED=10/100M Link、1000M=Gigabit Link) Port:(Orange=PoE LED+Green=Link LED)
Power Input	Built-in power AC: 100~240V 50-60Hz 2.1A
Operating Temperature/Humidity	-10 ~ +55°C ; 5% ~ 90% RH Non coagulation
Storage Temperature/Humidity	-40 ~ +75°C ; 5% ~ 95% RH Non coagulation

Data sheet

Product size/Packing size (L*W*H)	210mm*140mm*45mm 270*mm220mm*68mm
N.W/G.W (kg)	1.1kg/1.4kg
Installation	Desktop (optional wall +machine hanger parts)
Lightning protection level	3KV 8/20us ; IP30
Certificate	CE mark, commercial ; CE/LVD EN60950 ; FCC Part 15 Class B ; RoHS ; KC
Warranty	무상보증기간 1 년