


# Data sheet

<b>Model</b>	<b>SL-G3218SFP-8TP</b>
	
<b>18SFP+8TP L2 Managed Switch</b>	
Interface	18x SFP Port 8x 10/100/1000Mbps RJ45 Port
Console port	1*console port
Reset Key	1
Network Protocol	IEEE 802.3x IEEE 802.3、IEEE 802.3u、IEEE 802.3ab、IEEE 802.3z IEEE 802.3ad IEEE 802.3q 、IEEE 802.3q/p IEEE 802.1w、IEEE 802.1d 、IEEE 802.1S IEEE 802.3z 1000BASE-X STP(Spanning Tree Protocol) RSTP/MSTP (Rapid Spanning Tree Protocol) EAPS ring network protocol
Transmission Mode	Store and Forward
Bandwidth	56Gbps
Packet Forwarding	40.32Mpps
MAC Address	8K
Buffer	4.1M
FLASH	16M
RAM	128M
Watt	≤35W
LED Indicator	PWR: Power LED SYS:(System LED) 1~8:(Link LED=10/100M、1000M=Gigabit Link) 9-26:(SFP LED) MS:(Master power LED) SL:(Slave power LED)
Power	Built-in power AC 100~240V 50/60HZ
Operating Temperature/Humidity	-20~+55°C; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH Non coagulation
Product size	440mm*210mm*45mm
Weight	2.4kg

## Data sheet

Lightning protection level	3KV 8/20us; IP30
Certificate	CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS; KC
Warranty	1year

Software Parameter	
The following are the main software functions, not all, if there is no function, please consult us first! / Support software development with customized requirements!	
MAC Address	Support 16K MAC addresses;MAC address learning and aging
VLAN	Port-based VLANs Up to 4096 VLAN support Voice VLAN,can configure QoS for voice data 802.1Q VLAN
Spanning Tree	STP(Spanning tree protocol) RSTP(Rapid spanning tree protocol) MSTP(Rapid spanning tree protocol) EAPS(Ring network protocol) 802.1x argumentation agreement
Link Aggregation	Max 8 aggregation groups TRUNK , each supports 8 ports
Port Mirror	Many-to-one port mirroring
Loop Guard	Loop protection function, real-time detection, rapid alarm, accurate positioning, intelligent blocking, automatic recovery
Port Isolation	Support downlink ports isolated from each other and communicate with uplink port
Port Flow Control	Half duplex based back pressure control Full duplex based on PAUSE frame
Line Rate	Support downlink ports isolated from each other and communicate with upstream port
IGMP Snooping	IGMPv1/2/3 and MLDv1/2 GMRP Protocol Registration Multicast address management, multicast VLAN, multicast routing ports, static multicast addresses
DHCP	DHCP Snooping
Storm Suppression	Unknown unicast, multicast, unknown multicast, storm suppression of broadcast type Storm suppression based on bandwidth tuning and storm filtering
Security	User port+IP Address+MAC Address ACL based on IP and MAC Security properties of port based MAC address quantities
QOS	802.1p port queue priority algorithm Cos/Tos , QOS sign WRR (Weighted Round Robin) , Weighted priority rotation algorithm WRR、SP、WFQ , 3 priority scheduling models
Cable Sequence	Auto-MDIX; auto identification of straight-through cables and crossover cables
Negotiation Mode	Port supports automatic negotiation ( self-negotiation transmission rate and duplex mode)

## Data sheet

System Maintenance	Upgrade package upload System log view WEB restore factory configuration
Network Management	WEB NMS CLI management based on Telnet, TFTP, Console SNMP V1/V2/V3 RMON V1/V2 RMON Management